

# Liquid Filters

LL-142



# Dollinger LL-142 Liquid Filters

The Dollinger series LL-142 liquid filters are designed to remove final traces of dirt, pipe scale and other solid contaminants from process liquids

Unlike conventional multi-candle filters, the Dollinger element design concept maximises the effective filtration area for a given vessel size resulting in lower differential pressure and extended service life. In addition to the standard range of filters, Dollinger is able to offer customised filter designs and capacities to suit the particular process / application demands of the customer.

## HOUSING DESIGN AND CONSTRUCTION

As standard, the Dollinger LL-142 filter housing is designed and constructed in accordance with the ASME VIII, Division I Pressure Vessel construction code. In addition, Dollinger can also provide full design services to other pressure vessel codes e.g. BS5500, Stoomwezen, AD Merkbblätter, CODAP and AS 1210.

## MATERIALS OF CONSTRUCTION

The majority of our filters are constructed in Carbon Steel or Stainless Steel. However, we can also offer Duplex, Super Duplex and other high quality materials where required.

Special requirements for low temperature applications and/or for NACE specifications can also be accommodated.

## FILTER ELEMENT

The Dollinger LL-142 Filter incorporates the efficient radial fin element design which provides the largest filtration area for a given element size. This increases dirt holding capacity, minimises pressure drop and results in an extended service life.

The filter element support structure is constructed from steel suitable for the particular application. Standard element design ensures its integrity up to differential pressures of 3.45 bar and beyond, with special bespoke designs available where required.

## FILTER MEDIA

Dollinger offers an extensive range of synthetic and natural fibre filter media, suitable for use with most process liquids. In addition, stainless steel mesh media can be incorporated into the existing element design for more demanding applications. In most instances, the Dollinger filter element can be cleaned and re-used many times. This feature is especially beneficial in applications having high levels of contaminant.


## INTER-CHANGEABILITY

In the event of changing process conditions following installation, it is possible to interchange elements to vary the degree of filtration.



# Dollinger Design Concept

The Dollinger design concept combined with the radial finned element gives you these benefits :



Dollinger has up to 200 filter media available to cover service applications such as alkaline solutions, organic liquids, water, weak acids, bases, oxidizing agents, lube oils etc

## AVAILABLE OPTIONS


- Quick opening closures complete with pressure interlock device
- Davit assembly
- Support legs / brackets
- Weld neck flanged connections
- Earthing boss
- Customised paint specification

## ELEMENT CONSTRUCTION



### BASKET

Standard collapse pressure 1.5-4.0 Bar.  
Higher available when required.



### NOTCH RING AND WIRE

Used to form extended surfaces.  
Full use of filtration area and structural integrity



### MEDIA

Wide range to meet all service requirements.  
Positive sealing surface - minimum sealing area. Eliminate contaminant by-pass



## Global locations

### AMERICAS

#### SPX FLOW TECHNOLOGY

4647 S.W. 40th Avenue  
Ocala, FL 34474-5788  
United States  
P: 800 344 2611

#### SPX FLOW TECHNOLOGY

Brockville,  
ON K6V 7H7  
Canada  
P: 800 267 3884

#### SPX FLOW TECHNOLOGY MEXICO

APV Soluciones Integrales, SA de CV  
Parque Granada 71 piso 1  
Col. Parques de la Herradura  
Huixquilucan, Edo. De México  
P: +52 1 (81) 81619448

### EMEA

#### SPX FLOW TECHNOLOGY

IDA Business and Technology Park,  
Tiernaboul, Killarney,  
Co.Kerry,  
Ireland  
P: +353 64 6633322

#### SPX FLOW TECHNOLOGY AFRICA

Unit 12B  
Growthpoint Office Park, Tonetti Street  
Midrand,  
South Africa  
P: +27 11 207 3700

#### SPX FLOW TECHNOLOGY MIDDLE EAST FZE

P.O Box 299745,  
Downtown Jebel Ali  
The Galleries 4  
Dubai, U.A.E.  
P: +971 4 8143400

### APAC

#### SPX FLOW TECHNOLOGY

##### AUSTRALIA PTY LTD

7 Winton Street, Kewdale,  
Perth 6105, Western Australia  
P: +61 8 9353 6545

#### SPX FLOW TECHNOLOGY CHINA

No.666 FengJin Road,  
XiDu Industrial Park  
Feng Xian District  
Shanghai 201401, China  
P: +86 21 6715 8181

#### SPX FLOW TECHNOLOGY

##### SINGAPORE

25 International Business Park  
03-03/12 German Centre  
Singapore 609916  
P: +65 6264 4366

#### SPX FLOW TECHNOLOGY

##### INDIA PVT LTD

G-72/73 Riico Industrial Area  
Mansarovar  
Jaipur 302 020, India  
P: +91 141 239 8154

#### SPX FLOW TECHNOLOGY KERRY LTD

IDA Business and Technology Park,  
Tiernaboul, Killarney,  
Co.Kerry,  
Ireland

Phone: +353 64 6633322  
Fax: +353 64 6633371  
E-Mail: [sales.dollinger@spx.com](mailto:sales.dollinger@spx.com)

For more information, please visit [www.spx.com/en/dollinger](http://www.spx.com/en/dollinger)

SPX reserves the right to incorporate our latest design and material changes without notice or obligation.

Design features, materials of construction and dimensional data, as described in this bulletin, are provided for your information only and should not be relied upon unless confirmed in writing. Please contact your local sales representative for product availability in your region. For more information visit [www.dollinger-spx.com](http://www.dollinger-spx.com) and [www.spx.com](http://www.spx.com).

The green ">" is a trademark of SPX Corporation, Inc..